

OUTDOOR TEXTILE INDUSTRIAL SEWING THREAD

Profession in Sewing and Embroidery



DURAK TEKSTÝL is a manufacturer company of industrial sewing and embroidery thread that implements customer oriented solutions by facilitating innovative and experimenter high technologies. Products are being manufactured in its integrated manufacturing facilities particularly with its features of quality sustainability and service capabilities according to the requirements of the customers in global market. Durak sewing thread trademarks are being introduced to the market all over the world by means of its international sales network.

By following up developments in global sewing and embroidery sector we offer you, our business partners-solutions with high technology.

Durak Durabond UV: Continuous filament, high resistant polyester or polyamide structure is obtained as a result of application of the specific solution that is produced through an eco-friendly chemical formula developed by Durak Tekstil, on thread surface. Textile may be imposed the effects of salty water, UV lights, Sunlight, wind during its use in canvas, tent and tarpaulin which are undesired negative effects. Durak Durabond UV sewing threads provide maximum product safety against any thread wear at stitches that can be caused by UV Sunlight, salty water and wind.

Durak Durabond P UV sewing threads which are developed in order to be used in all types of sailcloth such as cenova(Flock), Mainsail, Mizenmast provided in various color and thickness to disposal of our esteemed customers.

OUTDOOR TEXTILE INDUSTRIAL SEWING THREAD

Profession in Sewing and Embroidery



DURABOND UV WR SEWING THREAD

Water repellent feature provided in the main thread structure enables the resistance of the thread against natural environment and climate changes to be provided at maximum level together with the specific bonded coating on the upper part. DURABOND UV WR Bonded sewing threads are 100% resistant against water absorption. Specific process applied to the structure of the thread to obtain-thread friction feature, and positive result were obtained after 100 hours friction test. Durak Durabond WR sewing threads are produced according to TSE standards and the product passed the test performed in order to determine the water repellent degree of the textile used with military purposes and made under heavy washing conditions, with success.

TECHNICAL INFORMATIONS FOR DURABOND UV WR SEWING THREAD

Sewing Thread	Ticket No	Type of Thread	Dtex/Ply	Strenght (cN)	Elongation %	Needle Size (Nm)
Durabond P UV	40	High Tenacity CF Polyester	290*3	4500	25-30	**
Durabond P UV	30	High Tenacity CF Polyester	350*3	5200	20-30	**
Durabond P UV	15	High Tenacity CF Polyester	845*3	10350	25-33	**
Durabond P UV WR	30 BP WR	High Tenacity CF Polyester	350*3	5150	20-30	**

Durak Quality Control Tests are performed according to ISO/TS 16949:2002 Standarts.

DURABOND UV WR SEWING THREADS FASTNESS INFORMATION

Fastness	Method	Durabond P UV
Light Fastness	TS 1008 EN ISO 105 B02	≥ 5
Wash Fastness	TS EN ISO 105-C06	≥ 4
Water Fastness	TS 396 PREN ISO 105-E01	≥ 4
Rubbing Dry Fastness	TS 717 EN ISO 105-X12	≥ 4
Perspiration Fastness	TS 389 PREN ISO 105-E04	≥ 4

USAGE RECOMMENDATIONS



Durak Tekstil has right to change technical specifications without any notice.

www.durak.com - sales@durak.com.tr

Sales & Marketing
DURAK Tekstil Pazarlama A.S.
 Phone : +90 212 468 06 00
 Fax : +90 212 468 06 99
 İstanbul Dünya Ticaret Merkezi
 A3 Blok K.14 No.430
 34149 Yeşilköy-İstanbul/TÜRKİYE

DURAK Poland
 Phone : +48 42 64 071 79
 Fax : +48 42 65 382 04
DURAK Spain
 Phone : +34 96 14 327 33
 Fax : +34 96 12 729 61

DURAK Austria
 Phone : +43 55 77 62 367
 Fax : +43 55 77 86 011
DURAK Germany
 Phone : +49 0180 321 39 40
 Fax : +49 0180 321 30 48

DURAK Shanghai
 Phone : +86 021 336 32 458
 Fax : +86 021 336 32 459
DURAK China
 Phone : +86 572 621 06 98
 Fax : +86 572 612 11 09